Cameras features

Camera type	
Product code	
Image sensor	Exmor™ Starvis™ CMOS Progressive Scan 1/2.8"
Lens	
Min. illumination	VSV
Electronic shutter	ZZ
Day & Night	R mo a l IR ut ilt
IR Illumination	t m a ti IR
PTZ	Pan 360° continuous rotation Tilt -5°–90° tical oom 30x

Video

Video compression	/ M PE
Resolution	WV
Frame rate	WVMWZ
Bitrate Video	IWZIWZ
WDR	
Streaming protocol	UPHZSPHZ
Streaming mode	SPWSLZLHPUNVUULPVUZOIUHPSZPLV WVMPSLZZWWVLMVHSPHUIHUPO VUMPNHPVU
Image settings	3D denoise, Brightness, Contrast, Sharpness, White balance, Saturation, Privacy mask, Defog, ROI, Text and Image Overlay, Rotation: mirror, flip, mirrro flip, Jlip, Mirror Jlip

Audio

Audio	VHMSSWSL
Audio compression	.
Audio connectors	

Network

Security	SPWSLZLHLZZSLLSZPOWHZZV WVLPVU/LUWPVU
Network protocols	IPv4, IPv6, Bonjour, TCP/ IP, DHCP, DNS, DynDNS, PPPoE, ARP, ICMP, FTP, SMTP, NTP, UPnP, RTSP, RTP, RTCP, HTTP, HTTPS, SSL, TCP, UDP, Bonjour, UPnP

System integration

Analytics	PVLLPVUHWLPUNLLPVU
Event triggers	SH
Event actions	LVR ZVHNL LNL ZVHNL - / LLU / HSH V WL HU WVZ LLUPHNL
Data streaming	PLVZLHLLUHH

Standard Features

Dimension	216x 44.4
Weight	6700g
Housing	SPUHSSV
Ingress protection	
Network connector	V
I/O	LPUHSISVR VLVUZWPVUH
LPHS VUULV	RS485
Power	VHH
VL connector	LPUHSSVR
Operating temperature	-6
Approvals	-V/
Language	HSPHUUNSPZOVLSHUNHNLWHRZVULZ

UNICA

VHSstorage	PV/ /
Event actions	Video recording to local storage
Installtion method	MHZSVR
System recovery	ILL
Wall mount	

spark

SPARK
VIA ANTONIO GRAMSCI, 86/A
42124 REGGIO EMILIA
P. +39.0522.1715150
F. +39.0522.1715151

P. IVA/C.F. 02542850355
R.E.A. di RE n. 291049

www.spark-security.com
info@spark-security.com

© 2013 - 2018 SPARK. All rights reserved. Unless expressly permitted in writing, no license is granted in relation to any copyright, industrial design, trademark, patent or other intellectual property rights of SPARK or its licensors. The information contained in this document may change without notice.document may change without notice.