

# NITIDA 2.0

## 3W Load

### AgfVaad: agef Y

EDŽAŽ ""#  
3^g\_ [ [g\_ US\_ Ws Zagef Y  
\$&HSU ;B(\*! ;=#"

<b>Housing</b>	Cast Aluminum
<b>Dimensions</b>	170mm(W)x502.8mm(L)x158.5mm(H)
<b>Weight</b>	5.1KG

### I S^4cSU Vfe

<b>Ingress Protection</b>	IP68
<b>Impact Resistant</b>	IK10
<b>Operating Temperature</b>	Working -50°C ~ 50°C Startup -40°C
<b>Window Heater ON/OFF</b>	≤ 20°C ON; ≥ 30°C OFF
<b>Cold Start Heater ON/OFF</b>	≤ 0°C ON; ≥ 5°C OFF
<b>Fan ON/OFF</b>	≥ 35°C ON; ≤ 25°C OFF



**SPARK HQ**  
Via Antonio Gramsci 86/A  
42124 Reggio Emilia, Italy  
Tel.: +39 0522 929 873  
[ Xa2 ebSd] ŽeWjdfkAb\_

**TAIWAN OFFICE**  
6F., No. 93, Shuiyuan St., East Dist.,  
30069 Hsinchu City, Taiwan  
Tel.: +886 3 575 2786  
[ XaSc[S2 ebSd] ŽeWjdfkAb\_

© 2013 - 2020 SPARK. All rights reserved. Unless expressly permitted in writing, no license is granted in relation to any copyright, industrial design, trademark, patent or other intellectual property rights of SPARK or its affiliates. The information contained in this document may change without notice document may change without notice.