

Pro-view Series

LUMINA 2MP

Pro-view series cameras are characterized by Spark patented smart backplate UNICA, allowing fast and effortless camera maintenance. They are the perfect balance between design and performance, with elegant housing that can withstand hostile environments.

- ▶ **PTZ network camera**
- ▶ **30x Optical Zoom**
- ▶ **Adaptive IR**
- ▶ **UNICA Smart Backplate**
- ▶ **Outdoor-Ready**
- ▶ **ONVIF Compliant**



Specifications

LUMINA 2MP
 ▶ SR-C-S2-LUMINA-V135-IR

Camera	Image Sensor	Sony Starvis CMOS Progressive Scan 1/2.8"
	Lens	Motorized 4.5 ~ 135mm, F1.6 ~ 4.4
	FOV	2.02° ~ 57°
	Day/Night	Automatically removable infrared-cut filter
	Min. Illumination	0.01Lux (Color) 0.001Lux (B/W)
	IR Illuminators	Adaptive IR up to 150 meters effective range
	Shutter Speed	1/5 ~ 1/5000s
	PTZ	Pan 360° continuous rotation Tilt -5° ~ 90° Optical zoom 30x
Video	Video Compression	H.265, H.264, MJPEG
	Resolution	1920x1080
	Frame Rate	Up to 30fps
	WDR	120dB
	Image Settings	3D Denoise, Brightness, Contrast, Sharpness, White Balance, Saturation, Privacy masks, ROI, Defog, Image Flip and Mirror, Text and image overlay
Audio	Audio Compression	G.711, G.726, AMR
	Audio Streaming	Two-way audio, full duplex
	Audio Interface	Line input and line output
Network	Security	Password protection, HTTPS encryption
	Protocols	IPv4, IPv6, Bonjour, TCP/ IP, DHCP, DNS, DynDNS, PPPoE, ARP, ICMP, FTP, SMTP, NTP, UPnP, RTSP, RTP, RTCP, HTTP, HTTPS, SSL, TCP, UDP, Bonjour, UPnP
System Integration	Analytics	Tampering detection, motion detection, audio detection
	Event Triggers	Analytics event, I/O alarms, periodical events, network link down
	Event Actions	Network storage, edge storage, FTP, SMTP, HTTP event, HTTPS, alarm out pre and post event image
	Wi-Fi Module	Yes
	Applications	Argo Video Management System, Spark Installer Mobile APP
	Interoperability	Onvif Profile S

Specifications

LUMINA 2MP ▶ SR-C-S2-LUMINA-V135-IR

General

Dimensions	428x216x275mm
Weight	6.7kg
Housing	Diecast aluminium, Plastic, Polycarbonate
Ingress Protection	IP66
Impact Protection	-
Certifications	CE, FCC
Edge Storage	-
Alarm I/O	Terminal block, - 12V DC, + 12V DC, GND
RS485	-
Network	RJ45 10/100
Power	PoE IEEE 802.3at, 12V DC, Terminal block
Operating Temperature	-30°C ~ 60°C

Accessories (optional)

Wall Mount	SR-O-U003 Wall mount to be used with UNICA
Pole Mount	SR-O-U004 Pole mount adapter to be used with UNICA

Outline Dimensions

Unit: mm

