

Pro-view Series

MIRA 2MP | 5MP | 4K

Pro-view series cameras are characterized by Spark patented smart backplate UNICA, allowing fast and effortless camera maintenance. They are the perfect balance between design and performance, with elegant housing that can withstand hostile environments.

- ▶ **Motorized Dome**
- ▶ **Video Analytics**
- ▶ **Adaptive IR**
- ▶ **UNICA Smart Backplate**
- ▶ **Outdoor-Ready**
- ▶ **ONVIF Compliant**



Specifications

		MIRA 2MP ▶ SR-C-S2-MIRA-V12-IR ▶ SR-C-S2-MIRA-V22-IR	MIRA 5MP ▶ SR-C-S5-MIRA-V10-IR	MIRA 4K ▶ SR-C-S8-MIRA-V10-IR
Camera	Image Sensor	Sony Starvis CMOS Progressive Scan 1/2.8"	Sony Starvis CMOS Progressive Scan 1/1.8"	Sony CMOS Progressive Scan 1/2.5"
	Lens	Motorized 2.8 ~ 12mm, Motorized 7 ~ 22mm, F1.4 ~ 2.8	Motorized 3.6 ~ 10mm, F1.5-2.8	Motorized 3.6 ~ 10mm, F1.3 ~ 2.4
	FOV	33° ~ 104° 14° ~ 43°	38° ~ 85°	38° ~ 95°
	Day/Night	Automatically removable infrared-cut filter		
	Min. Illumination	0.01Lux (Color) 0.001Lux (B/W)	0.05Lux (Color) 0.005Lux (B/W)	0.05Lux (Color) 0.005Lux (B/W)
	IR Illuminators	Adaptive IR up to 30 meters effective range		
	Shutter Speed	1/2 ~ 1/30,000s		
	Video	Video Compression	H.265, H.264, MJPEG	
Resolution		1920x1080	2560x1920	3840 x 2160
Frame Rate		Up to 60fps (WDR off) Up to 30fps (WDR on)	Up to 30fps	Up to 30fps
WDR		120dB		100dB
Image Settings		3D Denoise, Brightness, Color, Sharpness, White Balance, Compression, Exposure control (auto/manual), Privacy masks, ROI, Defog, Image Flip and Mirror, 90° and 270° Image Rotation, Text overlay		
Audio		Audio Compression	G.711 U law, a law, G.726, AMR	
	Audio Streaming	Two-way audio, full duplex		
	Audio Interface	Line input and line output		
Network	Security	Password protection, HTTPS encryption, digest authentication, IP filtering, Lock on login fails		
	Protocols	IPv4, IPv6, DHCP, DNS, DDNS, NTP, UPnP, Bonjour, Ping, SMB/CIFS, NFS, HTTP, HTTPS, RTP, RTSP, TCP, UDP, SSH		
System Integration	Analytics	Tripwire detection, perimeter detection, tampering detection, motion detection, crowd detection, audio detection		
	Event Triggers	Analytics event, I/O alarms, periodical events, network link down		
	Event Actions	HTTP/HTTPS, Email notification, video recording, snapshot, I/O notification		
	Wi-Fi Module	Yes		
	Applications	Argo Video Management System, Spark Installer Mobile APP		
	Interoperability	Onvif Profile S, T		

Specifications

MIRA 2MP
 ▶ SR-C-S2-MIRA-V12-IR
 ▶ SR-C-S2-MIRA-V22-IR

MIRA 5MP
 ▶ SR-C-S5-MIRA-V10-IR

MIRA 4K
 ▶ SR-C-S8-MIRA-V10-IR

General

Dimensions	160x160x163.5mm	
Weight	1.5kg	
Housing	Diecast aluminium, Plastic, Polycarbonate	
Ingress Protection	IP68	
Impact Protection	IK10	
Certifications	CE	CE, FCC
Edge Storage	MicroSD/SDHC/SDXC card slot	
Alarm I/O	2/1	
RS485	Yes	
Network	RJ45 10/100	
Power	PoE IEEE 802.3af, 12V DC, 2.5 to 12.5W, Terminal block	
Operating Temperature	-30°C ~ 60°C	

Accessories (optional)

Wall Mount	SR-O-U003 Wall mount to be used with UNICA
Pole Mount	SR-O-U004 Pole mount adapter to be used with UNICA

Outline Dimensions

Unit: mm

