



spark

Member of TTM TECHNOLOGY

# Nitida Series

**NITIDA 4K | 5K | 20MP**

Nitida is a cutting-edge real-time camera that boasts exceptional performance and delivers superior image quality, making it the ideal choice for capturing large spaces and every intricate detail. It is the first camera to offer an impressive 20MP @ 25FPS.

- ▶ **Box Camera**
- ▶ **Micro Four Thirds Lens Mount**
- ▶ **Embedded Video Analytics**
- ▶ **Dual MicroSD Card Slot & USB Port For External HDD**
- ▶ **ONVIF Compliant**



# Specifications

NITIDA 4K  
▶ SR-C-U9-NITIDA-M

NITIDA 5K  
▶ SR-C-U16-NITIDA-M

NITIDA 20MP  
▶ SR-C-U20-NITIDA-M

|                           |                   |   |           |           |
|---------------------------|-------------------|---|-----------|-----------|
| <b>Camera</b>             | Image Sensor      | Sony Exmor R CMOS Rolling Shutter Type 1  |           |           |
|                           | Lens              | Micro Four Thirds lens mount  |           |           |
|                           | FOV               | Depends on lens   |           |           |
|                           | Day/Night         | Automatically removable infrared-cut filter, light sensor   |           |           |
|                           | Min. Illumination | 0.01Lux (Color)<br>0.01Lux (B/W)  |           |           |
|                           | IR Illuminators   | 350m effective range (with SR-O-H002 IR illuminator)  |           |           |
|                           | Shutter Speed     | 1/2 ~ 1/20000s  |           |           |
| <b>Video</b>              | Video Compression | H.265, H.264, MJPEG   |           |           |
|                           | Resolution        | 4096x2160   | 5376x3024 | 5472x3648 |
|                           | Frame Rate        | Up to 25fps   |           |           |
|                           | WDR               | 100dB   |           |           |
|                           | Image Settings    | 2D/3D denoise, Brightness, Contrast, Sharpness, White balance, Saturation, Low light custom settings, Privacy mask, Defog, ROI, Text Overlay, Rotation: mirror, flip, mirror flip |           |           |
| <b>Audio</b>              | Audio Compression | G.711, G.726, AAC   |           |           |
|                           | Audio Streaming   | Two-way audio, full duplex  |           |           |
|                           | Audio Interface   | 3.5mm jack for mic., line input, line output  |           |           |
| <b>Network</b>            | Security          | Password protection, HTTPS encryption, digest authentication, dual boot, IP filtering, lock on login fails  |           |           |
|                           | Protocols         | IPv4, IPv6, DHCP, DNS, DDNS, NTP, UPnP, Bonjour, Ping, SMB/CIFS, NFS, HTTP, HTTPS, RTP, RTSP, TCP, UDP, SSH   |           |           |
| <b>System Integration</b> | Analytics         | Motion detection, Audio detection, AI Intrusion, AI Loitering, AI Tripwire, AI In/Out Count, AI Heatmap, AI People Density  |           |           |
|                           | Event Triggers    | Analytics event, I/O alarms, periodical events, network link down   |           |           |
|                           | Event Actions     | HTTP/HTTPS, video recording, snapshot, I/O notification   |           |           |
|                           | Applications      | Argo Video Management System, Spark Installer Mobile APP  |           |           |
|                           | Interoperability  | Onvif Profile S, T  |           |           |

# Specifications

NITIDA 4K  
▶ SR-C-U9-NITIDA-M

NITIDA 5K  
▶ SR-C-U16-NITIDA-M

NITIDA 20MP  
▶ SR-C-U20-NITIDA-M

## General

|                       |  |
|-----------------------|--|
| Dimensions            | 145x91x76mm  |
| Weight                | 0.9kg (without lens)   |
| Housing               | Diecast aluminium  |
| Ingress Protection    | IP68 (with SR-O-H001 outdoor enclosure)                                |
| Impact Protection     | IK10 (with SR-O-H001 outdoor enclosure)                                |
| Network               | RJ45 100/1000  |
| Edge Storage          | Dual MicroSD/SDHC/SDXC card slot (256GB), USB port 3.0 for HDD (10TB)  |
| Alarm I/O             | 2/1  |
| RS485                 | Yes  |
| Power Consumption     | Max: 30W (with SSD Device), Max: 15W (without SSD Device), Average: 6W |
| Power                 | PoE IEEE 802.3at, 12V DC, 24V AC, Terminal block                       |
| Operating Temperature | -10°C ~ 50°C   |
| Certifications        | CE, FCC  |

## Accessories (optional)

|                    |   |
|--------------------|---|
| Outdoor housing    | SR-O-H001 Enclosure and SR-O-H004 bracket. IP68, IK10, Built-in fan and heater. |
| IR illuminators    | SR-O-H002 IR illuminator 350m effective range, to use with SR-O-H001 enclosure. |
| Junction box       | SR-O-H003 Junction box. IP67, IK10, input 115/230VAC, output 24VAC 6A.          |
| Pole mount adapter | SR-O-H005 Pole mount adapter, to use with SR-O-H003 or SR-O-H004.               |
| Fixed bracket      | SR-O-0107 Indoor metal fixed 130mm wall/ceiling bracket.                        |
| Adjustable bracket | SR-O-0108 Indoor metal adaptable 300-470mm wall/ceiling bracket.                |

## Outline Dimensions

Unit: mm

